

List Users

Retrieve a list of users.

⚠ Attention

To prevent system performance issues that could occur due to large user databases, you must pass the `page` and `count` parameters to list paged results or the `filter` parameter to return results that match the filter criteria.

Query Parameters

filter (string)

- **Enum:** `"username"`, `"name.familyname"`, `"name.givenname"`
 - **Example:** `filter=name.familyname eq Admin or username eq sysadmin or name.givenname eq System`
 - **The criteria to filter the users list:**
 - **username** – The username of the user
 - **name.givenname** – The first name of the user
 - **name.familyname** – The last name of the user
 - **Supported operators:**
 - `eq` (equals)
 - `or` (match any of the specified criteria)
 - `and` (match all criteria simultaneously)
 - **Example Queries:**
 - Retrieve a single user: `?filter=username eq sysadmin`
 - Retrieve multiple users: `?filter=username eq sysadmin or username eq subadmin or username eq jdoe`
 - Returns all data for users that meet the filter criteria unless refined using the `properties` or `excludedProperties` parameters.
-

properties (string)

- **Enum:** `"meta"`, `"name"`, `"manager"`, `"addresses"`, `"emails"`, `"schemas"`, `"username"`, `"timezone"`, `"active"`, `"employeeNumber"`, `"organization"`, `"department"`, `"jobTitle"`
 - **Example:** `properties=schemas,emails`
 - The user properties to include in the return. Only use this parameter with the `filter` parameter.
 - **Note:** The return only includes specified properties and the following default data: `activePassword`, `activeEsig`, `changeNextLogin`, `siteId`, `internalId`, and `userId`.
 - **Tip:** Separate multiple properties with a comma. Do not include spaces.
-

excludedProperties (string)

- **Enum:** `"meta"`, `"name"`, `"manager"`, `"addresses"`, `"emails"`, `"schemas"`, `"username"`, `"timezone"`, `"active"`, `"employeeNumber"`, `"organization"`, `"department"`, `"jobTitle"`
 - **Example:** `excludedProperties=schemas,emails`
 - The user properties to exclude from the return. Only use this parameter with the `filter` parameter.
 - **Tip:** Separate multiple properties with a comma. Do not include spaces.
 - **Note:** If both `excludedProperties` and `properties` are provided, `excludedProperties` takes precedence.
-

page (integer <int32>)

- **Example:** `page=1`
- The page number for which to return results. Use this with the `count` parameter.

- **Note:**
 - This endpoint allows either paged results (`page` and `count`) or filtered results (`filter`).
 - Using both `page` and `filter` in the same request will result in an error.
- **Tip:** Use the `filter` parameter if you know the first name, last name, or username of the users you are trying to retrieve.

count (integer <int32>)

- **Example:** `count=100`
- The number of items returned per page. Use this with the `page` parameter.

Return

Returns a `UserList` object that contains `User` objects.

```
{
  "users": [
    {
      "name": "John Doe",
      "activePassword": true,
      "activeEsig": true,
      "changeNextLogin": false,
      "siteId": 12345678910,
      "internalId": 123456789,
      "userId": "JD0E",
      "properties": {
        "manager": "Jane Doe",
        "department": "Accounting"
      }
    }
  ]
}
```